



US006906747B2

(12) **United States Patent**
Okada

(10) Patent No.: **US 6,906,747 B2**
(45) Date of Patent: **Jun. 14, 2005**

(54) **ELECTRONIC CAMERA FOR PERFORMING GRADATION CONVERSION ON AN IMAGE SIGNAL**

(75) Inventor: **Sadami Okada, Sakado (JP)**

(73) Assignee: **Nikon Corporation, Tokyo (JP)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 839 days.

(21) Appl. No.: **09/913,062**

(22) PCT Filed: **Mar. 26, 2001**

(86) PCT No.: **PCT/JP01/02411**

§ 371 (c)(1),
(2), (4) Date: **Aug. 9, 2001**

(87) PCT Pub. No.: **WO01/76235**

PCT Pub. Date: **Oct. 11, 2001**

(65) **Prior Publication Data**

US 2004/0201757 A1 Oct. 14, 2004

(30) **Foreign Application Priority Data**

Apr. 3, 2000 (JP) 2000-101470

(51) **Int. Cl.⁷** H04N 5/217; H04N 5/202; G03F 3/08; G06K 9/00

(52) **U.S. Cl.** 348/241; 348/674; 348/254; 358/521; 382/169

(58) **Field of Search** 348/241, 242, 348/252, 253, 257, 250, 254, 255, 256, 606, 615, 627, 651, 674, 358/521; 382/167, 169

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,047,861 A * 9/1991 Houchin et al. 348/254
5,481,317 A * 1/1996 Hieda 348/254
5,517,333 A * 5/1996 Tamura et al. 358/521
5,708,729 A 1/1998 Adams et al.

5,859,927 A	1/1999	Adams et al.
5,974,190 A	* 10/1999	Maeda et al. 382/255
6,040,860 A	* 3/2000	Tamura et al. 358/521
6,160,532 A	* 12/2000	Kaburagi et al. 348/674
6,433,823 B1	* 8/2002	Nakamura et al. 348/254
6,433,838 B1	* 8/2002	Chen 348/674
6,697,127 B2	* 2/2004	Suzuki 348/674

FOREIGN PATENT DOCUMENTS

JP 07221987 A	* 8/1995	H04N/1/407
JP A-63-290028	11/1998	
JP 11170572 A	* 6/1999	B41J/2/21
JP 2000307939 A	* 11/2000	H04N/5/235
JP 2000354179 A	* 12/2000	H04N/5/20

OTHER PUBLICATIONS

Watanabe et al.; "Gradation Conversion by a Sigmoid Function in a Digital Camera System"; Japanese Hardcopy 2000 Collected Papers B-27; The Imaging Society of Japan.*

* cited by examiner

Primary Examiner—Wendy R. Garber

Assistant Examiner—John Villecco

(74) Attorney, Agent, or Firm—Oliff & Berridge, PLC

(57) **ABSTRACT**

The present invention performs gradation conversion linearly on an image signal when the image signal is darker than a preset value. Consequently, the dark region of the image is not distorted nonlinearly, and the gradations of shadows and hair can be reproduced in full richness. On the other hand, gradation conversion is performed nonlinearly on image signals if the image signal is brighter than a preset value. The nonlinear conversion in this case: (1) has a slope that effectively equalizes an average noise amplitude of the image signal without being based on the output gradation value, and (2) is offset so as to be continuous with the gradation conversion characteristic of the dark area gradation conversion unit. Through condition (1), the level-dependent noise in the bright region is equalized. Furthermore, through condition (2), gradation differences and gradation reversals do not occur at the boundary between the dark region and the bright region.

10 Claims, 8 Drawing Sheets

